

Product Specifications

FlashCheck. Certified Min/Max Dry Ice Thermometer

External Sensor Measurement Range	-115.6°F to 113°F (-82°C to 45°C)
Operating Range	14°F to 122°F (-10°C to 50°C)
Accuracy	±1.0°F from -58°F to 77°F (±0.5°C from -50°C to 25°C) ±2.0°F from -115.6°F to -59°F (±1.0°C from -82°C to -51°C) ±2.0°F from 78°F to 113°F (±1.0°C from 26°C to 45°C)
Display Resolution	0.1°F/°C
Display Reading Update	17 seconds
Display Size	1.92in W x 2.08in L (49mm W x 53mm L)
Instrument Size	2.99in W x 3.74in L x 0.74in D (76mm W x 95mm L x 19mm D)
Body Casing	ABS polymer, resistant to chemicals and high impact
Sensor	Thermistor
External Sensor	0.15in Dia x 0.98in (3.8mm Dia x 25mm) 3.28ft (1m) Teflon cable with stereo jack connector
Battery	AA Battery, user replaceable
Calibration	1-yr NIST Certification of Calibration at -70°C. Reference standards traceable to International System of Units (SI) through NIST.
Certification	CE mark, NIST traceable, RoHS, WEEE



Model

12239	Single external sensor with blunt tip probe and 1-yr NIST Certificate of Calibration at -70°C
12239-01	Single external sensor with blunt tip probe, includes ISO 17025/NIST Calibration Certificate

- Monitor vaccines in ultra-low temperatures down to -82°C
- Ideal for storage and transport with dry ice
- Minimum/Maximum memory for lowest and highest readings
- High and Low Alarms with audible buzzer and flashing red light
- Detachable external sensor with gold plated stereo jack connector
- Jumbo LCD
- Selectable °C/°F temperature scales
- Non-volatile memory retains settings during battery replacement
- Remaining battery indicator
- Mounts to vertical surfaces with strong built-in magnets
- Foldable stand for placement on flat surfaces

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 12239-X 20K3

