

Electrosurgical Generator & High Frequency Desiccator



Item Number: 570-0582

The Henry Schein Electrosurgical Generator is a High Frequency Desiccator with cutting ability. You might call it a split personality. One half of the unit is our Henry Schein High Frequency Desiccator. The other half is an Electrosurgical Generator, giving you 50 watts of cutting power and coag capabilities – plenty of power for most cutting procedures performed in the doctor's office.

High Frequency Desiccator with 50 watts of cutting capabilities

Two machines in one convenient package


Adjustable in 1/10th watt increments in the first 10 watts, for the most accurate output available

No grounding pad required when working in the desiccation mode

When in electrosurgical generator mode, the unit features NEM™ pad sensing technology which monitors the return electrode for optimum patient protection.



RELY ON US FOR QUALITY, SELECTION, PERFORMANCE, AND VALUE!



STANDARD EQUIPMENT

- 570-0582 (1) Henry Schein Electrosurgical Generator
- 895-0124 (1) 3-Button Autoclavable Handpiece
- 112-7171 (5) non-sterile sharp dermal tips
- 112-7172 (2) sterile sharp dermal tips
- 112-7173 (5) non-sterile blunt dermal tips
- 112-7175 (2) sterile blunt dermal tips
- 895-0127 (2) non-sterile DERM-Elite™ Premium blunt dermal tips
- 895-0126 (2) sterile DERM-Elite Premium blunt dermal tips
- 112-7176 (2) sterile disposable handpiece sheath
- 570-0331 (2) non-sterile disposable handpiece sheath
- 926-3686 (1) wall mount kit
- 110 VAC Hospital-grade power cord*
- User's guide*



895-0124



112-7171, 112-7172, 112-7173,
112-7175, 895-0127, 895-0126



926-3686



112-7176



570-0331

COMPLEMENTARY PRODUCTS †

† Sold Separately



102-7058
Table Top Stand †



600-5943
Footswitch †



570-0888, 570-0890
Sharp H-Type Tips †




570-0891, 570-0889
Blunt H-Type Tips †




118-3875
Force Cable †



147-2819
Reusable Bipolar Forceps †



Lletz Loop
Electrodes †



Resistick II Coated
Electrodes †



Tungsten Wire
Loop Electrodes †



330-8942
Mobile Stand †

OUTPUT POWER

- CUT: 50 WATTS
- BLEND: 50 WATTS
- COAGULATION: 50 WATTS
- FULGURATION: 40 WATTS
- BIPOLAR: 40 WATTS
- MICRO BIPOLAR: 40 WATTS

DIMENSIONS

- HEIGHT: 188MM (7.4 IN.)
- WIDTH: 228MM (8.98 IN.)
- DEPTH: 105MM (4.13 IN.)
- WEIGHT: < 2.26 KG (< 5 LBS.)

OUTPUT FREQUENCY

- 304 – 451KHZ
- LINE VOLTAGE**
- 570-0582: 100-240 VAC

LINE FREQUENCY

- 50HZ
- WARRANTY**
- FOUR YEARS

PRODUCT SPECIFICATIONS



RELY ON US FOR QUALITY, SELECTION, PERFORMANCE, AND VALUE!