

Extra comfortable with improved grip and skin moisturizing technology

- Features HYDRASOFT™ Technology to rehydrate dry and cracked skin and improve overall skin condition
- Soft material provides wearers exceptional comfort and ease of use
- Neoprene formulation and textured fingers deliver a secure, reliable wet grip
- Ultra-lightweight design for enhanced tactile sensitivity



Industries


- Healthcare
- Laboratory

Applications

- General dentistry
- Primary Care
- Patient examinations
- Protection from blood and other bodily fluids
- Intricate parts handling
- Preparing pharmaceutical products

HYDRASOFT™ Skin Moisturizing Technology

Glycerol additive absorbs and retains moisture in the epidermis



Dimethicone protective layer prevents skin from drying and cracking

TECHNICAL DATA SHEET

PRODUCT INFORMATION

Product	73-837 NeoSoft™
Material	Neoprene
Color	Light Green
Glove Design	Ambidextrous, Powder-Free, Polymer Coated, Textured Fingertips
Cuff	Beaded Cuff
Manufacturing/ QMS Audit Standards	ISO 9001 2008, 13485 2003/2012
Regulatory/Standards Compliance	D6977, CMDR, EN 420 2003, REACH, FDA21 CFR 177-2600
Standard Packaging	100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Indonesia
User Needs Segment	High Touch - Ultra-thin gloves that provide the highest level of tactile sensitivity, especially at the fingertip.

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUES					TESTING METHOD
	XS 5½-6	S 6½-7	M 7½-8	L 8½-9	XL 9½-10	
SIZE						ASTM D3767/EN 420
Length (mm / in)	240 / 9.5	240 / 9.5	240 / 9.5	240 / 9.5	240 / 9.5	
Average Palm Width (mm / in)	76 / 3.10	86 / 3.50	95 / 4.00	106 / 4.40	115 / 4.70	
Freedom from Holes (Inspection level I)	1.5 AQL					ASTM D5151/EN 374-2
Palm Thickness Single Wall	mm: 0.07 / mils: 2.8					ASTM D3767/EN 420
Finger Thickness Single Wall	mm: 0.09 / mils: 3.5					ASTM D3767/EN 420
	BEFORE AGING			AFTER AGING		
Ultimate Tensile Strength	17 MPa			14 MPa		ASTM D 412-06a
Elongation at Break (%)	500			400		ASTM D 412-06a

ORDERING INFORMATION

	SIZE	XS 5½-6	S 6½-7	M 7½-8	L 8½-9	XL 9½-10
73-837 NeoSoft™	REORDER NO.	73837060	73837070	73837080	73837090	73837100

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

*Warning: No glove provides complete protection against all chemicals. Users must test the gloves against the particular chemicals and environment in which they will be used.

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
T: +32 2 528 74 00
F: +32 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
(Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
63000 Cyberjaya
Selangor, Malaysia
T: +60 3 8310 6688
F: +60 3 8318 6699

North America Region

Ansell Healthcare Products LLC
111 Wood Avenue South,
Suite 210
Iselin, NJ 08830, USA
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial México S.A. de C.V.
Bvld. Bernardo Quintana No. 7001-C,
Q7001 Torre II.
Suites 1304, 1305 y 1306.
Col. Centro Sur, C.P. 76079
Querétaro, Qro. México
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16

Technology



Performance Standards

